WSC CONTAINER TYPE WAREHOUSES, FOR KTC / IBC CONTAINERS

Warehouses are calculated to accommodate IBC containers. Due to the appropriate additional equipment options (door type, fans, lighting), the warehouse is adapted to the consumer's needs for active storage of chemicals.



124.240.270



124.260.127



124.242.110

- Create to passive storage of hazardous substances in all hazard classes for KTC / IBC containers.
- Self-ventilation system ensures efficient ventilation of warehouse premises (0.4 times air exchange).
- The air vents are located directly above the drains on the pallet and in the upper part of the air vents.
- Active storage with an additional EX fan is available for more efficient removal of hazardous vapors (5x air exchange).
- Made of galvanized trapezoidal, RAL painted sheets (additional services).
- Door with cylindrical lock.
- Container depot with removable truss, made of 5 mm steel sheet, welded to WZ2.2 tightness, controlled in accordance with EN ISO571-1.
- The warehouse is equipped with a tripartite wall for leakage and spillage into the bottom.
- All construction is covered with high-quality anti-corrosion and waterproof coating according to EN ISO 12949-C3.
- Dibt Certificate, Ü.

The use of HDPE liners allows storage of acid



124.240.270



124.240.235



124.240.170

Certificates







Opening doors	124.260.127	124.260.227		
Sliding doors			124.260.154	124.260.254
Model	**WSC-F-E.1-27**	**WSC-F-E.2-27**	**WSC-F-E.1-54**	**WSC-F-E.2-54**
Number of rack levels	1	2	1	2
Spill bath capacity, L	1000 l	1000 l	2 x1000 l	2 x1000 l
KTC / IBC containers, pcs.	2	4	4	8
Outside dimensions LxWxH, mm	2820 x1450 x2190	2820 x1450 x3575	5580x1530x2245	5580 x1530 x3575
Internal section dimensions LxWxH,mm	2700 x1300 x1730	2700 x1300 x1450	2700 x1300 x1720	2700 x1300 x1450







Opening doors	124.240.135	124.240.235			
Sliding doors			124.240.170	124.240.270	124.240.370
Model	**WSC-F-E.1-35**	**WSC-F-E.2-35**	**WSC-F-E.1-70**	**WSC-F-E.2-70**	**WSC-F-E.2-110**
Number of rack levels	1	2	1	2	2
Spill bath capacity, L	1000 l	1000 l	2 x1000 l	2 x1000 l	3 x1000 l
KTC / IBC containers, pcs.	3	6	6	12	18
Outside dimensions LxWxH, mm	3500 x1450 x2245	3500x1450x3660	6940 x1530 x2245	7060 x1530 x3660	10380 x1540 x3660
Internal section dimensions LxWxH,mm	3380x1300x1795	3380 x1300 x1500	3380 x1300 x1730	3380 x1300 x1500	3380 x1300 x1500