WSC CONTAINER TYPE WAREHOUSES, WITH THERMOINSULATION

WSC thermally insulated container construction. It has been proven to be practically applied as an optimal solution for each application. All customer requirements can be met, regardless of whether the forklift truck is used or the customer needs a small container warehouse or a large container.



124.321.270 pasirinktinai nudažyti RAL spalva







CONSTRUCTION
Thermally insulated WSC containers are designed for industrial purposes. They can safely store temperature sensitive materials regardless of the outside temperature.

HEATING
WSC thermally insulated containers can be adapted to use most of the energy types available to the customer.

ISOLATION
As a rule, all walls, roofs and bottoms are completely insulated with thermal, hardly flammable or non-flammable sandwiches.

The use of HDPE liners allows storage of acid



• For storage of sensitive materials for temperature and humidity, all hazard classes.

• Design with external walls to protect against temperature drops and compensate for temperature fluctuations. Made of galvanized sheets, painted in RAL colors (optional).

• All side walls, roof, door and floor panels completely thermally insulated, mineral wool insulation - non-combustible A2 according to DIN 4102-1, insulation thickness at least 60 mm.

• Includes double door with cylindrical lock.

• Container depot with removable truss, made of 5 mm steel sheet, welded to WZ2.2 tightness, controlled in accordance with EN ISO571-1.

• All construction is covered with high-quality anti-corrosion water and resistant coating according to EN ISO 12949-C3.

• There are grate shelves at each storage level for convenient placement of constructions, containers or pallets.

• Dibt Certificate, Ü.



124.300.230

Certificates






124.300.230



124.300.360



Opening doors	124.300.130	124.300.230	124.300.330			
Sliding doors				124.300.160	124.300.260	124.300.360
Model	WSC-T-E.1-30	WSC-T-E.2-30	WSC-T-E.3-30	WSC-T-E.1-60	WSC-T-E.2-60	WSC-T-E.3-60
Number of rack levels	1	2	3	1	2	3
Spill bath capacity, L	450 l	450 l	650 l	2 x450 l	2x450 l	2x650 l
200 L barrels, pcs. ant grotelinių lentynų	10	20	30	20	40	60
200 l number of drums on chemical pallet	8	16	24	16	32	48
200 l number of drums on Euro pallet	6	12	18	12	24	36
Outside dimensions LxWxH, mm	3290 x1440 x2210	3290 x1440 x3180	3290x1440x560	6360 x1550 x2280	6360 x1550 x3180	6400 x1550 x4580
Internal section dimensions LxWxH,mm	3010 x1300 x1730	3010 x1300 x1250	3010 x1300 x1250	3010 x1300 x1730	3010 x1300 x1250	3010 x1300 x1250

Products for safe handling and storage of barrels with hazardous and flammable liquids, ensuring excellent protection of liquids, especially oil fluids or chemically aggressive liquids in case of spill and spill.



The warehouse is constructed according to the needs of the client, with additional side doors and shelves for storing buildings horizontally.



Warehouse with additional lighting and extended roof according to customer's request.

The use of HDPE liners allows storage of acid



WSC THERMAL INSULATED CONTAINER TYPE WAREHOUSE, FOR BARRELS STORAGE ON PALLETS

• For all hazard classes, temperature and humidity sensitive materials. Materials are stored in 60 L and 200 L drums on industrial and EUR pallets.

• Design with external walls to protect against temperature drops and compensate for temperature fluctuations. Made of galvanized sheets, painted in RAL colors (optional).

• Made of galvanized trapezoidal, lacquered sheets (additional service) RAL color.

• All side walls, roof, door and floor panels are fully thermally insulated, mineral wool insulation - non-combustible - A2 according to DIN 4102-1, with insulation thickness of at least 60 mm.

• Includes double door with cylindrical lock.

• Container depot with removable truss, made of 5 mm steel sheet, welded to WZ2.2 tightness, controlled in accordance with EN ISO571-1.

• All construction is covered with high-quality anti-corrosion water and resistant coating according to EN ISO 12949-C3.

• Dibt Certificate, Ü.



124.310.240

Certificates







124321270 optionally painted in RAL color













Opening doors	124.310.140	124.310.240	124.310.340			
Sliding doors				124.310.180	124.311.280	124.310.380
Model	WSC-T-E.1-30	WSC-T-E.2-30	WSC-T-E.3-30	WSC-T-E.1-60	WSC-T-E.2-60	WSC-T-E.3-60
Number of rack levels	1	2	3	1	2	3
Spill bath capacity, L	550 l	550 l	800 l	2 x550 l	2 x550 l	2 x800 l
200 l number of drums on chemical pallets	12	24	36	24	48	72
200 l - drums on Euro pallets	8	16	24	16	36	48
Outside dimensions LxWxH, mm	4180 x1480 x2205	4260 x1580 x3205	4260 x1580 x4585	8180 x1630 x2205	8260 x2950 x3180	8260 x1680 x4615

The use of HDPE liners allows storage of acid



WSC THERMAL INSULATED CONTAINER TYPE WAREHOUSE, FOR BARRELS STORAGE ON PALLETS

• For all hazard classes, temperature and humidity sensitive materials. Materials are stored in 60 L and 200 L drums on industrial and EUR pallets.

• Design with external walls to protect against temperature drops and compensate for temperature fluctuations. Made of galvanized sheets, painted in RAL colors (optional).

• Made of galvanized trapezoidal, lacquered sheets (additional service) RAL color.

• All side walls, roof, door and floor panels are fully thermally insulated, mineral wool insulation - non-combustible - A2 according to DIN 4102-1, with insulation thickness of at least 60 mm.

• Includes double door with cylindrical lock.

• Container depot with removable truss, made of 5 mm steel sheet, welded to WZ2.2 tightness, controlled in accordance with EN ISO571-1.

• All construction is covered with high-quality anti-corrosion water and resistant coating according to EN ISO 12949-C3.

• Dibt Certificate, Ü.



124.310.240

Certificates







124321270 optionally painted in RAL color



Opening doors	124.310.140	124.310.240	124.310.340			
Sliding doors				124.310.180	124.311.280	124.310.380
Model	WSC-T-E.1-30	WSC-T-E.2-30	WSC-T-E.3-30	WSC-T-E.1-60	WSC-T-E.2-60	WSC-T-E.3-60
Number of rack levels	1	2	3	1	2	3
Spill bath capacity, L	550 l	550 l	800 l	2 x550 l	2 x550 l	2 x800 l
200 l number of drums on chemical pallets	12	24	36	24	48	72
200 l - drums on Euro pallets	8	16	24	16	36	48
Outside dimensions LxWxH, mm	4180 x1480 x2205	4260 x1580 x3205	4260 x1580 x4585	8180 x1630 x2205	8260 x2950 x3180	8260 x1680 x4615

STORAGE OF IBC CONTAINERS, VERSIONS ISOLATED

• For all hazard classes, temperature and humidity sensitive materials. Materials stored in KTC / IBC containers

• Design with external walls to protect against temperature drops and compensate for temperature fluctuations. Made of galvanized sheets, painted in RAL colors (optional).

• Made of galvanized trapezoidal, lacquered sheets (additional service) RAL color.

• All side walls, roof, door and floor panels are fully thermally insulated, mineral wool insulation - non-combustible - A2 according to DIN 4102-1, with insulation thickness of at least 60 mm.

• Includes double door with cylindrical lock.

• Container depot with removable truss, made of 5 mm steel sheet, welded to WZ2.2 tightness, controlled in accordance with EN ISO571-1.

• All construction is covered with high-quality anti-corrosion water and resistant coating according to EN ISO 12949-C3.

• Dibt Certificate, Ü.



Possibility to order any configuration

The use of HDPE liners allows storage of acid



124.321.270 optionally painted in RAL color



124.330.227 with folding doors

Certificates













Opening doors	124.330.127	124.330.227		
Sliding doors			124.330.154	124.330.254
Model	**WSC-T-E.1-27**	**WSC-T-E.2-27**	**WSC-T-E.1-54**	**WSC-T-E.2-54**
Number of rack levels	1	2	1	2
Spill bath capacity, L	1000 l	1000 l	2 x1000 l	2 x1000 l
KTC / IBC containers, pcs.	2	4	4	8
Outside dimensions LxWxH, mm	2820 x1450 x2190	2820 x1450 x3575	5580x1530x2245	5700 x1530 x3575
Lentynų DIMENSIONS, LxWxH, mm	2700 x1300 x1730	2700 x1300 x1450	2700 x1300 x1720	2700 x1300 x1450











Opening doors	124.320.135	124.320.235			
Sliding doors			124.321.135	124.321.235	124.320.371
Model	**WSC-T-E.1-35**	**WSC-T-E.2-35**	**WSC-T-E.1-70**	**WSC-T-E.2-70**	**WSC-T-E.2-110**
Number of rack levels	1	2	1	2	2
Lygio keliamoji galia, L	1000 l	1000 l	2 x1000 l	2 x1000 l	3 x1000 l
KTC / IBC containers, pcs.	3	6	6	12	18
Outside dimensions LxWxH, mm	3500 x1450 x2245	3500x1450x3660	6940 x1530 x2245	7060 x1530 x3660	10380 x1540 x3660
Lentynų DIMENSIONS, LxWxH, mm	3380x1300x1795	3380 x1300 x1500	3380 x1300 x1730	3380 x1300 x1500	3380 x1300 x1500