HIWIN CONFIDENTIAL
機密文件未經許可，嚴禁複製

LMFA14 Linear Motor

Electrical specifications

	Symbol	Unit	Free air convection	Water cooling
Continuous force	F_c	N	544	1089
Continuous current	I_c	A_{rms}	5.4	10.8
Stall force	F_0	N	-	762
Stall current	I_0	A_{rms}	-	7.6
Peak force (1s)	F_p	N	2063	
Peak current (1s)	I_p	A_{rms}	33.5	
Force constant	K_f	N/A_{rms}	100.8	
Attraction force	F_a	N	3348	
Max. winding tempurature	T_{max}	℃	120	
Electrical time constant	K_e	ms	7.2	
Resistance (line to line ， 25℃)	R_{25}	Ω	4.2	
Resistance (line to line，120℃)	R_{120}	Ω	5.6	
Inductance (line to line)	L	mH	30.5	
Pole pair pitch	2τ	mm	30	
Back emf constant(line to line)	K_v	V_{rms}/(m/s)	58.2	
Motor constant (25℃)	K_m	N/√W	40.1	
Thermal resistance	R_{th}	℃/W	0.39	0.1
Thermal time constant	t_{th}	s	-	150
Thermal switch			1 x Pt1000 + 1 x (3 PTC SNM 120 In Series)	
Maximum velocity at maximum force	$V_{MAX,FP}$	m/s	3.44	
Maximum electric power input	$P_{EL,MAX}$	W	-	16461
Maximum dissipated heat output	$Q_{P,H,MAX}$	W	-	974
Max. DC bus voltage		V_{DC}	750	

Mechanical specifications

	Symbol	Unit	Free air convection	Water cooling
Mass of forcer	M_f	kg	7.6	
Unit mass of stator	M_S	kg	5.8	
Total installation height	H	mm	48.5	
Minimum flow rate		L/min	-	3.7
Temperature of cooling water		℃	-	20
Pressure drop	△P	bar	-	2.13
Water temperture difference	$\triangle\theta_{P,H}$	K	-	3.8

Lf	mm	460	Wf3	mm	81.5
Lf1	mm	367.5	Wf4	mm	43
Wf	mm	96	Wf5	mm	20
Wf1	mm	33	N	mm	8
Wf2	mm	30	n	mm	-

F-V curve







Focer dimensions



Mounting tolerance



Stator dimensions



Type	Ls	Ls1	Ls2	Ls3	Hs	Hs1	Ws	Ws1	N
LMF1S1	120	122.77	30.6	60	11.8	5.9	88	74	2
LMF1S1E	120	122.77	30.6	60	11.3	5.7	88	74	2
LMF1S2	180	182.77	30.6	120	11.8	5.9	88	74	3
LMF1S2E	180	182.77	30.6	120	11.3	5.7	88	74	3
LMF1S3	300	302.77	30.6	240	11.8	5.9	88	74	5
LMF1S3E	300	302.77	30.6	240	11.3	5.7	88	74	5

Except dimensions, all the specifications in the table are in ±10% of tolerance

Version: 2.00

Date: 2020/5/8